

INVOICE TO CITY OF NAPOLEON

Curbing and/or Sidewalk replacement

Location of project 549 W Maumee Ave Nap

Owner of Property Donald Buehler 551 W Maumee Ave Nap
address

Napoleon Ohio 43545 419-599-0687
City Zip Phone

Type of work performed: Curbing replacement _____ Sidewalk replacement X

Total length of curbing replaced _____ x \$20.00 ----- \$ _____

Total square footage of sidewalk replaced 1942 ^{sq ft} x \$1.50 ----- \$ 276.00

Total to be reimbursed to the owner ----- \$ _____

The City may reimburse the owner for sidewalk replacement in the right of way at a rate of one dollar and fifty cents (\$1.50) per square foot, if installed in accordance to City specification. The City will reimburse the owner for curbing replacement in the right of way at a rate of twenty dollars (\$20.00) per linear foot, if installed in accordance to City specification.

Name of City registered contractor who performed such work; (If none involved mark "Self")
self City Lic.# _____

Donald Buehler _____
Signature of property owner Date 5-22-08

The work referenced herein has been performed in accordance with the City of Napoleon minimum requirements and therefore is eligible for reimbursement accordingly.

City Engineer Date

City Purchase order number RG080745 City Permit number _____

pd 8/5/08



M&R Redi-Mix, Inc.



READY MIXED CONCRETE • AGGREGATE
SUPPLIES • CUSTOM TRUCKING
1 - (800) 786-6325

521 Commercial Street
Pettisville, OH 43553
PH: (419) 445-7771

5601 Cherry Street
Stony Ridge, OH 43463
PH: (800) 786-6325

County Road 1-C
McClure, OH 43534
PH: (419) 748-8442

MAILING ADDRESS
BOX 53038
PETTISVILLE, OHIO 43553

CAUTION

May cause eye or skin injury. Contains Portland cement. Freshly mixed cement, mortar, concrete, or grout may cause skin injury.

TAKE THESE PRECAUTIONS:

1. Avoid all contact with eyes.
2. Wear rubber boots and gloves, and avoid prolonged contact directly with skin or through porous materials.
3. In case of contact with skin or eyes. **FLUSH THOROUGHLY WITH WATER.**
4. If irritation persists, get medical attention promptly.
5. Keep children away.

TERMS AND CONDITIONS

This load of concrete is produced in accordance with the A.S.T.M. standard specifications for Redi-Mix concrete.

We do not guarantee finished results obtained from this load of concrete, as many important factors affecting the ultimate quality of the completed job are out of our control.

Excessive water in concrete reduces its final strength. Any water added to the mix on the job will be at the purchaser's risk.

Ready Mix concrete is not returnable for credit.

In the event of delivery beyond curb line, this company will not assume liability for damage to curbs, sidewalks, driveways or other personal property.

Estimated delivery schedules will be maintained to the best of our ability. We will not consider any claims for damages for failure to do so.

Customer will be allowed 6 minutes per yard unloading time. Overtime price will apply to any additional time.

Water added: _____ Gallons

Customer's representative

LEAVE PLANT	ARRIVE JOB	START POUR
FINISH POUR	LEAVE JOB	ARRIVE PLANT

CUSTOMER ID	P.O. NUMBER	ZONE	JOB NUMBER	TIME	DATE	TICKET	
MISC02				3:20 PM	23-Jul-08	14361	
SOLD TO DON BUEHLER			DELIVER TO DON BUEHLER 551 W MAUMEE RD AVE W. OF GRACEWAY				
QUANTITY THIS LOAD	QUANTITY ORDERED	QUANTITY DELIVERED	PRODUCT SPEC	PRODUCT DESCRIPTION	UNIT OF MEASURE	UNIT PRICE	EXTENDED PRICE
4.25	4.25	4.25	SSAIR	6 SK AIR-ENT	yd	\$93.50	\$397.38
1.00	1.00	1.00	28F	FUEL SURCHARGE	/L	\$30.00	\$30.00
CHAD	02	4.00					
TRUCK	PLANT	SLUMP	DUE AT JOB	USE OF CONCRETE	SUB-TOTAL		
CALCIUM	AIR ENTRAIN	SUPER PLAS.	ACCELERATOR		TAX		\$427.38
						TOTAL	\$455.16

DELIVERY INSTRUCTIONS

SPECIAL INSTRUCTIONS

TEAR HERE

Truck	Driver	User	Disp	Ticket Num	Ticket ID	Time	Date
76	CHAD	user			14361	15:20	7/23/08
Load Size	Mix Code	Returned	Qty	Mix Age	Seq	Load ID	
4.25 yd	SSAIR				D	15242	
Material	Design Qty	Required	Batched	% Var	Moisture	Actual Wat	
57's-CUSTAR	1564 lb	6680 lb	6660 lb	-0.31%	0.50% M	4 gl	
ZNS-HS6	1405 lb	6140 lb	6090 lb	-0.82%	2.75% M	20 gl	
LAF-TYP1	550 lb	2338 lb	2344 lb	0.28%			
PRO-PROAIR	1.40 /C	32.73 oz	33.00 oz	0.84%			
Water #1	34.0 gal	120.0 gal	120.0 gal	-0.01%		120.0 gl	
Actual	Num Batches: 1						
Load Total:	16098 lb Design W/C:	Water/Cement:	0.513 A	Design Water:	0.0 gl	Actual Water:	144.1 gl To Add: 0.0 gl
Slump:	4.00 in Water in Truck:	0.0 gl	Adjust Water:	0.0 gl/Load	Trim Water:	0.0 gl/ yd	Note: Manual feed occurred



Redi-Mix, Inc.

READY MIXED CONCRETE • AGGREGATE
SUPPLIES • CUSTOM TRUCKING
1 - (800) 786-6325



521 Commercial Street
Pettisville, OH 43553
PH: (419) 445-7771

5601 Cherry Street
Stony Ridge, OH 43463
PH: (800) 786-6325

County Road 1-C
McClure, OH 43534
PH: (419) 748-8442

MAILING ADDRESS
BOX 53038
PETTISVILLE, OHIO 43553

CAUTION

- may cause eye or skin injury. Contains Portland cement. Freshly mixed cement, mortar, concrete, or grout may cause skin injury.
- TAKE THESE PRECAUTIONS:**
- Avoid all contact with eyes.
 - Wear rubber boots and gloves, and avoid prolonged contact directly with skin or through porous materials.
 - In case of contact with skin or eyes. **FLUSH THOROUGHLY WITH WATER.**
 - If irritation persists, get medical attention promptly.
 - Keep children away.

TERMS AND CONDITIONS

This load of concrete is produced in accordance with the A.S.T.M. standard specifications for Redi-Mix concrete.

We do not guarantee finished results obtained from this load of concrete, as many important factors affecting the ultimate quality of the completed job are out of our control.

Excessive water in concrete reduces its final strength. Any water added to the mix on the job will be at the purchaser's risk.

Ready Mix concrete is not returnable for credit.

In the event of delivery beyond curb line, this company will not assume liability for damage to curbs, sidewalks, driveways or other personal property.

Estimated delivery schedules will be maintained to the best of our ability. We will not consider any claims for damages for failure to do so.

Customer will be allowed 6 minutes per yard unloading time. Overtime price will apply to any additional time.

Water added:

Gallons

Customer's representative

LEAVE PLANT	ARRIVE JOB	START POUR
FINISH POUR	LEAVE JOB	ARRIVE PLANT

CUSTOMER ID	P.O. NUMBER	ZONE	JOB NUMBER	TIME	DATE	TICKET	
MISC02				3:20 PM	23-Jul-08	14361	
SOLD TO DON BUEHLER			DELIVER TO DON BUEHLER 551 W MAUMEE RD AVE W. OF GRACEWAY				
QUANTITY	QUANTITY	QUANTITY	PRODUCT	PRODUCT	UNIT OF MEASURE	UNIT PRICE	EXTENDED
THE LOAD 4.25	ORDERED 4.25	DELIVERED 4.25	SSAIR	FUEL SURCHARGE	yd	\$93.50	\$397.38
1.00	1.00	1.00	28F		/L	\$30.00	\$30.00
CHAD	02	4.00					
TRUCK	PLANT	SLUMP	DUE AT JOB	USE OF CONCRETE			
CALCIUM	AIR ENTRAIN	SUPER PLAS.	ACCELERATOR				
						SUB-TOTAL	
						TAX	\$427.38
						TOTAL	\$427.78

DELIVERY INSTRUCTIONS

SPECIAL INSTRUCTIONS

\$455.16
\$455.16

TEAR HERE

Truck	Driver	User	Disp	Ticket Num	Ticket ID	Time	Date
76	CHAD	user			14361	15:20	7/23/08
Load Size	Mix Code	Returned	Qty	Mix Age	Seq	Load ID	
4.25 yd	SSAIR				D	15242	
Material	Design Qty	Required	Batched	% Var	Moisture	Actual Wat	
57's-CUSTAR	1564 lb	6680 lb	6660 lb	-0.31%	0.50% M	4 gl	
2NS-HSG	1405 lb	6140 lb	6090 lb	-0.82%	2.75% M	20 gl	
LAF-TYP1	550 lb	2338 lb	2344 lb	0.28%			
PRO-PROAIR	1.40 /C	32.73 oz	33.00 oz	0.84%			
Water #1	34.0 gal	120.0 gal	120.0 gal	-0.01%		120.0 gl	
Actual Num Batches:	1						
Load Total:	16090 lb Design W/C:		Water/Cement: 0.513 A	Design Water:	0.0 gl	Actual Water:	144.1 gl To Add: 0.0 gl
Slump:	4.00 in	Water in Truck:	0.0 gl	Adjust Water:	0.0 gl/Load	Trim Water:	0.0 gl/ yd Note: Manual feed occurred