FROM :TRI COUNTY FAX NU. :4153555002
FRUM CITY OF NAPOLEON 419 599 8393

P 2

CITY OF NAPOLEON OHIO PERMIT APPLICATION THES APPLICATION SEFOR RECEIPED BY LUDBON BUILDING, RECHANICAL DEMOLITION, REMODELING

· · · · · · · · · · · · · · · · · · ·	REPORTIAL CONTRUCTION INCLUDING BUILDING, RECTRICAL PLUMBING, MECHANICAL DEMOLITION, KEMODELING
DATE 1-10-2003	JOB LOCATION 1125 STEVENSON
	SUBDIVISION NAME
OWNER SCOTT WILL	STOLLOW HOME 419-242-9467
CONTRACTOR Tri-Cou	Stevenson cry Napoleon zie 19512435
CONTRACTOR ADDRESS 13	unty Roofing, Inc. PHONE 419-399-3964 171 C.R. 142 CITY Paulding ZIP 45879
	-399-9462 CELL PHONE (Opt.)
DESCRIPTION OF WORK TO BE	PERFORMED: -total rehab
ESTEMATED COST OF WORK TO	OBE PERFORMED: 17,1000
	JEFERFORMED: 1 1,1000
WORK INFORMATION	
BUILDING: Basement Floor Area	Sq. Ft. 1st Story Living Area Sq. Ft.
2nd Floor Living Area	Sq. Ft. Garage Floor Area Sq. Ft.
BUILDING SIZE: Length	Width Stories Height DEMO VOL
Masonry Contractor	Height DEMO VOL
Address	City Phone Fax Zip
Electrical Contractor	Phone
Physica Co.	City Phone Fax Zip
Plumbing ContractorAddress	City St Zip
Acdress	City Phone Fax
Insulation Contractor	
Address	CityFax
Other Contractor attach information.	
ZONING INFORMATION (to be com	ipleted by City): District Lot Dimension
LOX AFCS FRSB	poletted by City): District Lot Directsions SYSB RYSB Max Ht R Max Cov % poletted Coder as Ordinances wade performing the work have described districted by Max Ht Max Cov %
selected by the property meta-area of the CIO of Newclade.	poleon Codes as Orchanous wade parforming the work harm described. Understand that all work for which a permit is instead in required to be
opplicant Signature ONDO	Haynes Date 7-10-03
4	
Dermit # 1754	1)
Louin	

Scott Wiler Unit# DP4 City of Napoleon Down Pay Assist. Kenab Spec's 1125 Stevenson Napoleon, Ohio 43545 phone (419)242 - 9467 L Exterior doors: Replace each the front, south side, and garage entry doors with Stanley, Therma-Tru, or equal quality pre-hung insulated steel doors with light. Doors must be factory painted or contractor applied (TWO coats). Homeowner to select door style and color from contractor options (garage entry must be soil panel). Contractor must repair all damage incurred from door replacement. Install Kwikset-Belaire Series or equal quality lockset with dead-bolt locks. Locks must be keyed alike. 456 Keinsten Z Stors (2. Rooling: Remove all of the garage roof shingles, down to the sheathing. Affix 15# felt to roof decking and secure atuminum drip edge to roof perimeter edges. Install, per manufacturer's instruction, minimum 240# test weight/ Class A fire rated/ 30 year warranty/ fiberglass dimensional roof shingles. Homeowner to select shingle color. 3. Replacement windows: Wrap all of the exterior window and door trim with formed aluminum coil stock materials. Hameowner to select coll frim color. Install white vinyl replacement windows (Certainteed, Seaway, Great Lakes, or equal quality) to all of the windows throughout the structure. NOTE- The interior and exterior perimeters must be properly caulked with window/door

4. Electrical:

Electrical Service - Install a 100 amp service entrance, complete with weather head, boot flash, mast, and meter. Locate at the south exterior wall of the home (outside the office/nurscry).

Electrical Panel - Install a 100 amp/ twenty space electrical breaker panel and properly wire, bond, ground, and label. Locate panel in the office/nursery on the south wall.

Electrical wiring - Replace all ungrounded electrical wire throughout the entire structure with properly sized and grounded wire. Replace all devices (i.e switches/receptacles) with U.L. approved devices.

Replace the air conditioner electrical feed with properly sized electrical wire, with ground.

Bathroom - GFCI protect the TWO(2) receptacles at the vanity area.

Utility - Place furnace wire in conduit.

Replace the furnace fuse (located at control switch) with 15 amp fuse.

Kitchen - Install a range hood vent, with light, directing exhaust to the homes exterior. Locate above the stove/oven.

GFCI protect all of the counter receptacles.

Install TWO (2) additional gfci protected receptacles. Locate at each the east wall (south of stove) and at the west end of bar/counter.

Livingroom - Install electrical wire feed and ONE (1) 8' length electric baseboard heater with individual thermostat control to heat the area.

Install ONE (1) additional wall receptacle. Locate at the west wall (south of stairs).

Bedroom #1 (2nd floor/east) - Install TWO (2) additional wall receptacles. Locate at each the east wall and south wall.

Install electrical wire feed and ONE (i) 8' length electric baseboard heater with individual thermostat control to heat the area.

2nd floor landing - Install TWO (2) additional wall receptacles. Locate at each the west wall and south wall.

Smoke detectors - Install FOUR (4) U.L. approved, hardwired smoke detectors with battery back-up. Wire detectors in series. Locate at each of the following locations.. hallway (near kitchen), office/nursery, bedroom #2, and stair landing (top).

CO detector - Install ONE (1) U.L approved hardwired, with battery back-up CO detector. Locate in the hallway, outside the utility room.

Exterior - GFCI protect the garage wall receptacle on the south wall. Install a wall switched light fixture in the garage attic, near the ladder access.

Install TWO (2) exterior gfci receptacles, complete with weather resistant cover Locate ONE (1) at each the front and side entry.

NOTE: All electrical work must conform to NEC and be performed by qualified technician(s).

5. Plumbing:

Bathroom - Install gated shut-off valves to the vanity water supply lines.

Utility - Replace the clothes washer drain trap with ABS "p" trap.

Repair the cold water supply line and faucet at the sink, to allow water flow/operation.

PL-9,00 Exterior - Install a frost-proof exterior sill cock with vacuum break. Install at existing spigot location

6. HVAC: Perform a routine service (clean and tune) to the heating system. Service to include: oiling of the blower, replacement of defective belts, adjustment of belts, adjusting the blower, adjustment of pilot, replacing defective thermocouple, cleaning of pilot/heat exchanger/burner compartment, filter replacement, adjusting of the main burners for efficiency.

NOTE: Furnace work must be performed by a qualified furnace technician.

7. Miscellaneous carpentry:

Garage - Install, per manufacturers instruction, wooden pull down attic access ladder. Locate at existing access opening in the garage.

FROM : TRI COUNTY

9 F

Bed #1 (2nd floor/east) - Install a pre-finished birch interior door slab, complete with privacy 256 passage door knob, to the existing opening.

Insulation - Affix 2" rigid insulation to the interior perimeter of foundation block.

Properly secure R-19 batt insulation to the perimeter rim and sill joists.

TOTAL PROJECT BID 7.600

161 Rt

400M.

Contractor Tr. County



Scott Wiler 1125 Stevenson Napoleon, Ohio 43545

City of Napoleon Down Pay Assist. Rehab Spec's

phone (419)242 - 9467

steven 800

1. Exterior doors: Replace each the front, south side, and garage entry doors with Stanley, Therma-Tru, or equal quality pre-hung insulated steel doors with fight. Doors must be factory painted or contractor applied (TWO coats). Homeowner to select door style and color from contractor options (garage entry must be soil panel). Contractor must repair all damage incurred from door replacement.

Install Kwikset-Belaire Series or equal quality lockset with dead-bolt locks. Locks must be keved alike.

2,400 - 34

2. Roofing: Remove all of the garage roof shingles, down to the sheathing. Affix 15# felt to roof decking and secure aluminum drip edge to roof perimeter edges. Install, per manufacturer's instruction, minimum 240# test weight/ Class A fire rated/ 30 year warranty/ fiberglass dimensional roof shingles. Homeowner to select shingle color.

3. Replacement window: Wron all of the exterior window and door trim with formed aluminum coil stock materials. Homeowner to elect coil trim color Install white vinyl replacement windows (Certainteed, Scaway, Freat Nikes, or equal quality) to all of the windows throughout the structure. NOTE- The interior and exterior perimeters must be properly caulked with window/door

caulk.

4. Electrical:

Electrical Service - Install a 100 amp service entrance, complete with weather head, boot flash, mast, and meter. Locate at the south exterior wall of the home (outside the office/nursery).

Electrical Panel - Install a 100 amp/ twenty space electrical breaker panel and properly wire, bond, ground, and label. Locate panel in the office/nursery on the south wall,

Electrical wiring - Replace all ungrounded electrical wire throughout the entire structure with properly sized and grounded wire. Replace all devices (i.e switches/receptacles) with U.L. approved devices.

Replace the air conditioner electrical feed with properly sized electrical wire, with ground.

Bathroom - GFCI protect the TWO(2) receptacles at the vanity area.

Utility - Place farnace wire in conduit.

Replace the furnace fuse (located at control switch) with 15 amp fuse.

Kitchen - Install a range hood vent, with fight, directing exhaust to the homes exterior. Locate above the stove/oven.

2 · d

418-784-2061

d1+:60 60 80 Inc MAPO

GFCI protect all of the counter recentacles.

Install TWO (2) additional gfci protected receptacles. Locate at each the east wall (south of stove) and at the west end of bar/counter.

Livingroom - Install electrical wire feed and ONE (1) 8' length electric baseboard heater with individual thermostat control to heat the area.

Install ONE (1) additional wall receptacle. Locate at the west wall (south of stairs).

Bedroom #1 (2nd floor/east) - Install TWO (2) additional wall receptacles. Locate at each the east wall and south wall.

Install electrical wire feed and ONE (1) 8' length electric baseboard heater with individual thermostat control to heat the area.

2rd floor landing - lustall TWO (2) additional wall receptacles. Locate at each the west wall and south wall.

Smoke detectors - Install FOUR (4) U.L. approved, hardwired smoke detectors with battery back-up. Wire detectors in series. Locate at each of the following locations.. hallway (near kitchen), office/nursery, bedroom #2, and stair landing (top).

CO detector - Install ONE (1) U.L. approved hardwired, with battery back-up CO detector. FL- \$7.00 Locate in the hallway, outside the utility room.

Exterior - GFCI protect the garage wall receptacle on the south wall. Install a wall switched light fixture in the garage attic, near the ladder access. Install TWO (2) exterior gfci receptacles, complete with weather resistant cover. Locate ONE (1) at each the front and side entry.

NOTE: All electrical work must conform to NEC and be performed by qualified technician(s).

5. Plumbing:

Bathroom - Install gated shut-off valves to the vanity water supply lines.

Utility - Replace the clothes washer drain trap with ABS "p" trap.

Repair the cold water supply line and faucet at the sink, to allow water flow/operation.

Exterior - Install a frost-proof exterior sill cock with vacuum break. Install at existing spigot location.

6. HVAC: Perform a routine service (clean and tune) to the heating system. Service to include: oiling of the blower, replacement of defective belts, adjustment of belts, adjusting the blower, adjustment of pilot, replacing defective thermocouple, cleaning of pilot/heat exchanger/burner compartment, filter replacement, adjusting of the main burners for efficiency.

NOTE: Furnace work must be performed by a qualified furnace technician.

7. Miscellaneous carpentry:

Garage - Install, per manufacturers instruction, wooden pull down attic access ladder. Locate at existing access opening in the garage.

E . 9

Bed #1 (2nd floor/cust) - Install a pre-finished birch interior door slab, complete with privacy passage door knob, to the existing opening.

Insulation – Affix 2" rigid insulation to the interior perimeter of foundation block. Properly secure R-19 batt insulation to the perimeter rim and sill joists.

1850 BU

TOTAL PROJECT BID

17.600-

* 13600 1900 24